INSPECTION CERTIFICATE

VIDEO

PORTABLE LEEB HARDNESS TESTER WITH WIRELESS PROBE
CODE HDT-WP201

- Wireless digital probe
- Universal testing angle, no need to set impact direction
- Based on Leeb (HLD), converted to Vickers (HV), Brinell (HB), Rockwell (HRC, HRB, HRA), Shore (HS) and tensile strength (MPa)
- Dual value display, shows both Leeb and converted hardness
- Large LCD display with backlight
- Can choose large font display and statistics display
- Automatically calculate maximum, minimum and average value
- Save 300 data
- Operation temperature: -10°C~45°C
- According to ASTM A956, DIN 50156





hardness test block D (included)



small support ring (included)



bluetooth printer (**optional**)

SPECIFICATION

Resolution	1HLD/1HV/1HB/0.1HRC/0.1HRB/ 0.1HRA/0.1HS/1MPa
Accuracy	±6HLD (when HLD=800)
Measuring range	170-960HLD, 17-70HRC, 13-109HRB, 20-655HB, 80-940HV, 32-99.5HS, 30-88HRA, 255-2180MPa
Power supply	2×AA batteries
Dimension (L×W×H)	135×77×32mm
Net weight	240g



large font display



statistics display

STANDARD DELIVERY

Main unit	1 pc
Hardness test block D	1 pc
Small support ring	1 pc
Cleaning brush	1 pc
Impact device D	1 pc

OPTIONAL ACCESSORY

Impact device DC	**HDT-WL320-DCW**
Impact device C	**HDT-WL320-CW**
Impact device DL	**HDT-WL320-DLW**
Impact device G	**HDT-WL320-GW**
Hardness test block D**	**HDT-B-HLD3**
Hardness test block G*	**HDT-B-HLG2**
Bluetooth printer	**ISH-LP200-PRINTER**
Support rings	page 47

* Hardness test block G (**HDT-B-HLG2**) is for probe G (**HDT-WL320-GW**)
** Hardness test block D (**HDT-B-HLD3**) is for all others probes



DC (**optional**) C (**optional**) D (included) DL (**optional**) G (**optional**)

APPLICABLE WORKPIECE

Impact device		**DC**	**C**	**D**	**DL**	**G**
Application		inner wall of small space	small or thin workpiece, coating layer	general use	narrow slot or small hole	casting or forging workpiece
Maximum roughness of workpiece (Ra)		2μm	0.4μm	2μm	2μm	7μm
Minimum weight of workpiece	**direct measurement**	5kg	1.5kg	5kg	5kg	15kg
	on solid support	2kg	0.5kg	2kg	2kg	5kg
	coupled on plate	0.05kg	0.02kg	0.05kg	0.05kg	0.5kg
Minimum thickness of workpiece		3mm	1mm	3mm	3mm	10mm